Dart Aerospace Ltd. Wednesday, 12/6/2006 10:39:32 AM Date: Eric Charbonneau User: **Process Sheet** : INITIAL PROTOTYPE TEMPLATE Customer : CC-DAR01 Dart Aerospace Ltd. **Drawing Name** Job Number : 00064A **Estimate Number** : 10068 : INITIAL PROTOTYPE D3542-1 P.O. Number **Part Number** : 12/6/2006 This Issue S.O. No. : **Drawing Number** : AC0002 Prsht Rev. : NC Project Number First Issue : 11/28/2006 : PURCHASED PARTS **Drawing Revision** : 00063A Previous Run **Material** Each Due Date : 6/21/2006 Qty: 1 Um: Written By Checked & Approved By Comment : Project #: Description: Additional Product Job Number: Description: Seq. #: Machine Or Operation: 1.0 MFG ENGINEERING MFG ENGINEERING Comment: Setup: 0.00Hrs/ Run: 0.0000Hrs Total Run: 0.0000Hrs pout on workerset pur Dug D3542 MOBILOS MFG ENGINEERING Manufacture Prototype as per Dwg's Supplied By Engineering Comments: Bore to Linish size per Dwg D3542 Grap FZ 06.12.06

2.0 PG

PURCHASING





Comment: Setup: 0.00Hrs/ Run: 0.0000Hrs Total Run: 0.0000Hrs

PURCHASING

Attached certificate of conformity for raw material and subcomponents use for this w/o

Date: Wednesday, 12/6/2006 10:39:33 AM Eric Charbonneau User: **Process Sheet** Drawing Name: INITIAL PROTOTYPE TEMPLATE Customer: CC-DAR01 Dart Aerospace Ltd. Job Number: 00064A Part Number: INITIAL PROTOTYPE Job Number: Seq. #: **Machine Or Operation:** Description: 16.0 MS24693C272 Screw comment: Qty.: 1.0000 Each(s)/Unit Total: 1.0000 Each(s Screw 17.0 MS24693C273 Screw Somment: Qty.: 1.0000 Each(s)/Unit Total: 1.0000 Each(s) Screw 18.0 **ENGINEERING 1 ENGINEERING RESOURCE #1** Comment: Setup: 0.00Hrs/ Run: 0.0000Min Total Run: 0.0000Hrs **ENGINEERING RESOURCE #1** 07-03.15 Approval of project manager 19.0 DC DOCUMENT CONTROL DOCUMENT CONTROL N-67-15 Inspection Level 21 Job Completion

Form: rprocess


Page 4


-W/0.

PRELIMINARY ISSUE


				00/0					
7	DESIGN DRAWN BY			DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA					
	CHECK	KED	APPROVED	DRAWING NO.	REV. A				
	8.7 8.7			D3542	SHEET 1 OF 1				
(15°3)	DATE			TITLE	SCALE				
,		06.1	1.20	BRACKET	2:3				
	REV		DATE	DESCRIPTIO	N				
	Α		06.11.27	NEW ISSUE					

UNDER REVIEW





D3542-1 BRACKET



NOTES

1) MATERIAL: 6061-T6 ALUMINUM BAR PER QQ-A-225/8 OR QQ-A-200/8 OR AMS 4117/4128/4115/4116/4160 (REF DART SPEC M6061T6B)

2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1

POWDER COAT GREY SANDTEX (4.3.5.6) PER DART QSI 005 4.3

3) TOLERANCES ARE PER DART QSI 018 UNLESS ÓTHERWISE NOTED

4) IDENTIFY WITH DART P/N "D3542-1" USING FINE POINT PERMANENT INK MARKER

5) ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED

6) BREAK ALL SHARP EDGES 0.005 TO 0.010 MAX

COPYRIGHT © 2006 BY DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.

DART AEROSPACE LTD	Work Order: N/A				
Description: Barochet		Part Number: D3540-1			
Inspection Dwg: Rev:		Page 1 of 1			

FIRST ARTICLE INSPECTION CHECKLIST

		First Artic	le _	Proto	type			
Drawing Dimension	Tolerance	Actual Dimension	Accept	Reject	Method of Inspection	Comments		
3.750	±.030	3.750	/					
2.500	1.010	2.502						
1,000	1.010	,998	/					
0.500	5.010	,498	/					
0,50	7,030	,510	J					
1.00	+,030	1,020	/					
Ø.266	7.006 7.001	.265	/					
\$2,010	+ .005	2.011	/					
\$2.500	±.010	2.501						
Q.025		,025						
.06 ×45°								
				ļ				
						•		

Measured by:	Audited by:	J.L	Prototype Approval:	
Date: 07/03/14	Date:	07/03/14	Date:	07.03.15

Rev	Date	Change	Revised by	Approved
A	ijij.	New Issue	KJ/RF	

		i	1	ı						
	1	i	i	İ						
	;		•	İ				1		
	1	:	1	i i						
•	į		į.	1						
	Ţ.		· · ·	: Orio						
i e	Į.		**						2	
	í		1				94 1	8		
	:		İ							
		1	į	I		ê y				
	*		i. 1							
	!		į	İ						
	ļ		÷ 1					•		
				Ì						
	i.		1			· ·	**			••
			Ţ	İ						
<u>.</u>			· i		,		g *			
- · · · · ·	P ^{T1}			1				*		
	1			Ţ						
	(4)		· ·	ļ						- ;
	1	:	it .							

	COPPER & BRASS						0030	1902	OH 5	582115		
	400 RENAISSANCE	CENT	ER		90.00	05.110		INVOICE	DATE			
	SUITE 1900				INVO	CE NO.	-50	* /	/			
	DETROIT		MI 48	3243	0000	S WEIGHT		B/L NO.	/	DAT	E SHIPPED	
					GROS			149372		/	/	
	COPERT & PRICE		TNG G		VIA	3852		147372		,	,	
	COPPER & BRASS		, INC C			איינים איינים	P TRUCK	•				
	6700 POE AVENUE				F.O.B		P IROCK					
	ኮ አ ፕፖጥር እ፤		OH 45	5414	1	EST	N					
	DAYTON CUSTOMER P.O. NO.			NTRACT NO.		IORIZED SIGN						
	C48524		3011.00	1777-01-710.	-	- /	2 0	10 1			man military are a plane as participated in	
		ts as follows			1	en	Soul					
			SB 221-99	9	TO	OM G.	SMALL		12/1	1/03		
_			Q-A-200/8		AED	MANAGER O	QUALITY ASSURAI	NCE				
·	XX	~	~		<u></u>			-L -averad by th	his report has	been inspected	and tested	
	MEETS T6 TEMPER	REQU	IREMENTS		acco	rdance with I	the Sellers stand	ara samping p	han book for	und to meet	the applicat	
	6061-T6511 O	RDERI	TEM		requ	of the material described in this report and has been found to meet the applied the material described in this report and has been found to meet the applied the material meta						
	ASTM B 221 SUPE	RIOR	QUALITY	PLATE	com	position limits nal contamina	s and had the me ant in aluminum :	alloys. Neither	Mercury nor a	ny of its compo	ounds are us	
	ORDER NUMBER	1	ALLOY AND TE	MPER	in th	e manufactur	mits and had the mechanical properties shown. Also, note that maint in aluminum alloys. Neither Mercury nor any of its compount of the compoun					
	582115	606	1-T6511	and the second		Alcoa Engineered Products						
	ITEM	ITEM DE	SCRIPTION		PR	PRODUCT QUANTITY SHIPPED CODE PCS., FT., ETC. OR AS INDICATED						
	001 C/P 089551				RO	R04010 22 3834 //24/0.						
	ACC-U-PLATE	3				PC 264.9 CAPULY SURV						
	1.000(+.038		0)X12(+.	168/-0								
	SEC 510989					1	FT	Fill Control		hur segan		
	LEN 12' 1/	′2"			- 1		_ 3	Mari Car	- XOO	6023	5 4	
	WFC (W	14.48	31 F 02 C	12.10)		BNDLS	From Co			المصافحات مرتسبونات	
			DEFF					A TERROR NUMBER	++	13/7		
			neren	ENCE OF	VLY	- '		MANAAT		zwiele Leit	galler Handrick State (1997) (1997) Handrick State (1997)	
			4 4		4.4			WGT_S		PCS	at .	
								Mari	de-C	A Store	manaconnecentario (a)	
				· · · · · · · · · · · · · · · · · · ·				A distance of the same			-	
				MECH	ANICAL PRO		(Ttol 1	Witte	Carl St	£**	
		RACK	RACK **			TRENGTH KSI*		CONDUCTIVITY		ELONG % IN 2" OR 4		
	LOT NUMBER	FROM/TO	NUMBER OF TESTS	TENS		MIN.	ELD***	MIN.	MAX.	MIN.	MAX.	
	500335 001	A /B	1	MIN. 46.4	MAX. 46.4	44.8	44.8	1,,,,,,	III) D.V.	10.3	10.3	
	582115-001	А / Б	1	40.4	40.4	11.0						
	F (2)	,										
										*		
					-							
		5.5	9.00							1		
8	* :							3.71	. 19	1		
	•							A		<u> </u>		
		<u> </u>		ALDOCITION IN I	DEDCENT MA	YIRAHIM LINE E	SA SHOWN AS A	RANGE				

CHEMICAL COMPOSITION IN PERCENT MAXIMUM UNLESS SHOWN AS A RANGE

ALLOY SILICON IRUN COPPER MANGANESE MAGNESIUM CHROMIUM ZINC TITANIUM 6061 0.40-0.8 0.7 0.15-0.40 0.15 0.8-1.2 0.04-0.35 0.25 0.15

OTH/EACH OTH/TOT ALUMINU 0.05 0.15 REMAINDE

* KIPS PER SQUARE INCH. ONE KIP EQUALS ONE THOUSAND POUNDS.
** WHEN 2 OR MORE TESTS PER RACK ARE MADE, THE HIGHEST AND LOWEST VALUES ARE REPORTED.
*** YIELD STRENGTH IS DETERMINED BY THE 0.2% OFFSET METHOD.

Alcoa Extrusions, Inc.